



Powerful imaging plus a long list of productivity features.

Kodak i200 Series Scanners



Kodak is changing your expectations for desktop production scanning.

- Simplex (i250) and duplex (i260 and i280) models for colour, bitonal and greyscale imaging
- Perfect Page Scanning with iThresholding delivers sharp, clean images without rescanning
- SurePath paper handling and 3-D ultrasonic multi-feed detection minimise jams and let you scan with confidence
- Scan extremely long and irregularly shaped documents with the i280 Scanner
- Toggle Patch lets you easily switch between bitonal and colour scanning "on the fly"
- Optional dockable flatbed and document imprinter
- Easy setup and operation
- Worldwide service and support for your peace of mind



KODAK Capture Software,
Lite



Features and Benefits

Exceptional speed, image quality and flexibility. Fast scanning, automatic image processing and five output options mean you can scan up to 248 images per minute at 200 dpi. Choose from colour, bitonal, greyscale, simultaneous bitonal and greyscale or simultaneous bitonal and colour output.

Perfect Page Scanning with iThresholding: Advanced image processing from Kodak allows you to scan even poor-quality documents and get great images. Image cropping and straightening happen at full scanning speed. We've virtually eliminated the need to rescan or change settings so that you can be more productive, automatically.



Competitive scanner



Perfect Page Scanning with iThresholding, only from Kodak

Exclusive SurePath paper handling is designed for smooth paper transport and virtually jam-free operation.

Electronic Colour Dropout allows you to optimise forms processing by removing irrelevant red, green or blue background colour.

Innovative options to meet more scanning needs:

- Dockable flatbed handles exception documents and offers space-saving flexibility.
- Post-scan imprinter lets you track documents after scanning.

Brightness and Contrast Control allows customised colour output for different applications.

VRS compatibility offers more imaging options.

Long-lasting, mercury-free Xenon lamps reduce downtime and operating costs.

Standard IEEE-1394 (FireWire) interface speeds your images on their way. For your convenience, the IEEE-1394 card and cable are included.

Bundled KODAK Capture Software, Lite, plus ISIS and TWAIN drivers, lets you start scanning right away.

Toggle Patch lets you automatically switch back and forth between bitonal and colour scanning "on-the-fly" as often as needed, simply by scanning a unique patch code.

3-D multi-feed detection with ultrasonic technology lets you scan with confidence.

i280 Scanner only:

Long document mode allows you to scan exception documents (such as electrocardiograms and seismographic charts) up to 6.1 m and beyond—even documents a mile long—depending on PC memory.

Special document mode allows you to auto-feed even the most irregularly shaped documents.

Specifications

Recommended Daily Volume	i250/i260: Up to 5,000 pages per day i280: Up to 7,500 pages per day
Throughput Speeds* (Landscape, A4, Bitonal Greyscale, Colour) ppm = pages/minute (simplex) ipm = images/minute (duplex)	i250 (simplex)/i260 (duplex): 150 dpi resolution, 67 ppm/134 ipm 200 dpi resolution, 50 ppm/100 ipm 300 dpi resolution, 33 ppm/67 ipm i280 (duplex): 150 dpi resolution: 81 ppm/162 ipm 200 dpi resolution: 62 ppm/124 ipm 300 dpi resolution, 37 ppm/74 ipm
Scanning Technology	Single Tricolour Plus CCD (i250); Dual Tricolour Plus CCD (i260/i280) Greyscale output bit depth is 256 levels (8-bit) Colour capture bit depth is 40-bit (10 bits per red, green, blue and black channels) Colour output bit depth is 24-bit
Optical Resolution	300 dpi
Illumination	Single 2500 hour+ Xenon lamps
Output Resolution	75/100/150/200/240/300/400/600 dpi
Maximum Document Size	i250/i260: With 64 MB of on-board memory: 297 mm x 432 mm With 256 MB of on-board memory: 297 mm x 660 mm i280: With 256 MB of on-board memory: 297 mm x 863 mm In long document mode: 203 mm x 6.1 m Dockable flatbed accessory: 297 mm x 432 mm
Minimum Document Size	89 mm x 64 mm
Paper Thickness and Weight	Onionskin to card stock
Feeder	Automatic Document Feeder for continuous loading of up to 150 sheets of 60 g/m ² paper
Multi-feed Detection	3-D ultrasonic multi-feed detection
Connectivity	IEEE-1394 (FireWire) Interface (card & cable included); 6-pin connector
Bundled Software	TWAIN and ISIS drivers; KODAK Capture Software, Lite
Imaging Features (in the scanner)	Perfect Page Scanning with iThresholding, Autocrop, Aggressive Crop, Deskew, Electronic Colour Dropout, Halftone Removal, Noise Removal, VRS Compatible
On-board Compression	CCITT Group IV; JPEG or uncompressed output
File Format Outputs (from Bundled Drivers)	JPEG (for colour and greyscale images) TIFF (for bitonal images)
Warranty	Standard: 12 months, on-site. Extended: 3 year, on-site option
Electrical Requirements	100-240 V; 50-60 Hz; universal power supply included
Power Consumption	Running: 100W typical, 180W maximum, ENERGY STAR: <12W
Environmental Factors	ENERGY STAR qualified scanners Mercury-free Xenon lamps Operating humidity: 15% to 76% RH Operating temperature: 15-35° C
Acoustical Noise (operator position Sound Pressure level)	Standby mode: 39.7 dB(A) Operating mode: 57.0 dB(A)
PC Configuration	Minimum: PENTIUM III 1 GHz processor, 256 MB RAM Recommended: PENTIUM IV 2.4 GHz processor, 512 MB RAM
Supported Operating Systems	WINDOWS 98SE, Me, 2000, XP
Memory	i250/i260: 64 MB DIMM installed in the scanner (will support up to 256 MB) i280: 256 MB DIMM installed in the scanner
Approvals and Product Certifications	UL 60950 3rd Edition, C-UL CAN/CSA-C22.2 No. 60950-00 3rd Edition, TUV EN 60950, CE Mark, 47 CFR Part 15 Subpart B (FCC) Class A, ICES-003 Issue 3 Class A, EN 55022:98 Class B**, EN 61000-3-2 Powerline Harmonics, EN 61000-3-3 Flicker, EN 55024, AS/NZS 3548 Class A (C-Tick Mark), CNS 13438 Class A, VCCI Class A, CISPR 22 Class B**
Consumables Available	Feed module, separator module, imprinter ink cartridge and blotters, calibration targets
Accessories	Dockable flatbed, post-scan document imprinter

Specifications subject to change without notice. Throughput speeds may vary depending on your choice of driver, application software, operating system and PC. *With an optimal PC configuration (3.0 GHz processor, 512 MB RAM), the i280 model can achieve 40 ppm at 300 dpi. **Class A when optional dockable flatbed is attached.

For more information visit: www.kodak.com/go/scanners

As an ENERGY STAR® Partner, Eastman Kodak Company has determined that these products meet ENERGY STAR® guidelines for energy efficiency.

We're here for you.
Kodak Service & Support

Dockable Flatbed:

- Weight: 7.3 kg
- Length: 643 mm
- Width: 486 mm
- Height: 162.5 mm



- Weight i250: 12.5 kg
i260/i280: 13.9 kg
- Depth: 287 mm
- Width: 625 mm
- Height: 354 mm



CONTACT INFORMATION

EASTMAN KODAK COMPANY. Document Imaging, Rochester, New York 14650 +1-800-944 6171
KODAK (AUSTRALASIA) PTY. LTD. Document Imaging, North Ryde NSW 2113, AUSTRALIA +61-2-9870-4224
KODAK (CHINA) INVESTMENT COMPANY LIMITED. Document Imaging, CHINA
Beijing +8610-6561-6561 ext 8908, Shanghai +8621-6350-0888 ext 1297,
Guangzhou +8620-8666-9888 ext 6406, Shenyang +8624-2281-2988 ext 4016.
KODAK (HONG KONG) LIMITED. Document Imaging, North Point HONG KONG +852-2564-9330
KODAK INDIA LIMITED. Document Imaging, INDIA
Chennai +91-44-2362-1203, New Delhi +91-11-2338-5471, Mumbai +91-22-5641-6751
KODAK (KOREA) Limited. Document Imaging, Seoul, KOREA +82-2-708-5549
KODAK (MALAYSIA) SDN BHD. Document Imaging, Selangor MALAYSIA +603-7957-2722 x 1381
KODAK (PHILIPPINES) LIMITED. Document Imaging, Makati City PHILIPPINES 1299 +632-810-0331 x 322
KODAK (SINGAPORE) PTE. LTD. Document Imaging, SINGAPORE 098632 +65-6371-3168
KODAK TAIWAN LIMITED. Document Imaging, Taipei TAIWAN 112 +886-2-2316-8188
KODAK (THAILAND) LIMITED. Document Imaging, Bangkok THAILAND 10400 +662-271-304-059 x 404
In other areas of Asia, contact Kodak via email: marcom@kodak.com



Innovation you can count on™

© Eastman Kodak Company, 2005.
Kodak is a trademark of Eastman Kodak Company.

A-5739 CAT No. 817 2561 Printed in Australia 04/05