

Kodak

i200 series scanners



Powerful and productive imaging

Kodak is raising your expectations for desktop production scanning by delivering powerful imaging plus a long list of productivity features. Perfect Page scanning makes scanned images sharp while SurePath paper handling maximises productivity. With the i280 Scanner, you can auto-feed extremely long and irregularly shaped documents.

The optional dockable flatbed and document imprinter give you even more versatility.

Incredibly clear images

- Perfect Page scanning automatically delivers clean, sharp images at full speed
- Electronic colour dropout for red, green or blue for optimized forms processing
- Get black&white, greyscale or colour output, plus two dual stream output: black&white and greyscale or black&white and colour.

Maximum productivity

- 3 scanner models: i250 (simplex), i260 (duplex) and the premium i280 (duplex)
- Scan up to 124 images per minute at 200 dpi. With dual stream up to 248 images per minute (see technical data for details)
- SurePath paper handling and ultrasonic multi-feed detection let you scan with confidence
- IEEE-1394 (**FireWire**) interface for fast image transfer (card and cable included)
- Optional dockable flatbed handles exception documents
- Optional document imprinter
- The i280 Scanner can scan documents up to 6.1 m and beyond – even a mile long – depending on PC memory
- The toggle patch feature on the i280 model lets you automatically switch between black&white and colour scanning “on the fly” as often as needed, simply by scanning a unique patch code

Kodak PerformancePlus for i200 series scanners

The PerformancePlus service contract is designed to meet your specific business needs. It helps protect your productivity and keeps your scanner performing optimally while protecting your budget.

- On-site manufacturer’s service and support
- 3 years parts & labour total coverage
- Scanner consumables are included
- A Kodak engineer will visit the site within 8 hours
- If your scanner cannot be fixed it will be replaced with a brand new scanner at no charge
- Free 4th year service coverage if there have been no service calls in first three years



Kodak i200 Series Scanners

Specifications

Recommended Daily Volume	i250/i260: Up to 5,000 pages per day, i280: Up to 7,500 pages per day
Throughput Speeds* (landscape, A4, bitonal, greyscale, colour) ppm = pages/minute (simplex) ipm = images/minute (duplex)	i250 (simplex)/i260 (duplex): Up to 67 ppm/134 ipm at 150 dpi, up to 50 ppm/100 ipm at 200 dpi i280 (duplex): Up to 81 ppm/162 ipm at 150 dpi, up to 62 ppm/124 ipm at 200 dpi (Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.)
Scanning Technology	Single Tricolour Plus CCD (i250); Dual Tricolour Plus CCD (i260/i280), Greyscale output bit depth is 256 levels (8-bit) Colour capture bit depth is 40-bit (10 bits per red, green, blue and black channels), Colour output bit depth is 24-bit
Optical Resolution	300 dpi
Illumination	Single long-life Xenon lamp
Output Resolution	75/100/150/200/240/300/400/600 dpi
Maximum Document Size	i250/i260: With 64 MB of on-board memory: 297 mm x 432 mm With 256 MB of on-board memory: 297 mm x 660 mm i280: With 256 MB of on-board memory: 297 mm x 863 mm In long document mode: 203 mm x 6.1 m Dockable flatbed accessory: 297 mm x 432 mm
Minimum Document Size	89 mm x 64 mm
Paper Thickness and Weight	Onionskin to card stock
Feeder	Automatic Document Feeder for continuous loading of up to 150 sheets of 60 g/m ² paper
Multi-feed Detection	Multi-feed detection with ultrasonic technology
Connectivity	IEEE-1394 (FireWire) Interface (card and cable included); 6-pin connector
Bundled Software	TWAIN and ISIS drivers; Kodak capture software, lite
Imaging Features (in the scanner)	Perfect Page scanning; iThresholding, autocrop, aggressive crop, deskew, electronic colour dropout, dual stream scanning, halftone removal, noise removal, VRS compatible
On-board Compression	CCITT Group IV; JPEG or uncompressed output
File Format Outputs (from bundled drivers)	JPEG (for colour and greyscale images), TIFF (for bitonal images)
Electrical Requirements	100-240 V; 50-60 Hz; universal power supply included
Power Consumption	Running: 100W typical, 180W maximum, Energy Star: <12W
Environmental Factors	Energy Star qualified scanners, Mercury-free Xenon lamps Operating temperature: 15-35° C, Operating humidity: 15 to 76 percent relative humidity
Acoustical Noise (operator position sound pressure level)	Standby mode: 39.7 dB(A) Operating mode: 57.0 dB(A)
PC Configuration	Minimum: Pentium III 1GHz processor, 256 MB RAM, Recommended: Pentium IV 2.4 GHz processor, 512 MB RAM
Supported Operating Systems	Windows 98SE, Windows Me, Windows 2000, Windows XP, Windows Vista by the end of 2007
Memory	i250/i260: 64 MB DIMM installed (will support up to 256 MB), i280: 256 MB DIMM installed
Approvals and Product Certifications	UL 60950 3rd Edition, C-UL CAN/CSA-C22.2 No. 60950-00 3rd Edition, TUV EN 60950, CE Mark, 47 CFR Part 15 Subpart B (FCC) Class A, ICES-003 Issue 3 Class A, EN 55022:98 Class B**, EN 61000-3-2 Powerline Harmonics, EN 61000-3-3 Flicker, EN 55024, AS/NZS 3548 Class A (C-Tick Mark), CNS 13438 Class A, VCCI Class A, CISPR 22 Class B**
Consumables Available	Feed module, separator module, imprinter ink cartridge and blotters, calibration targets
Accessories	Dockable flatbed, post-scan document imprinter
Dimensions (scanner)	Weight: i250 - 12.5 kg, i260/i280 - 13.9 kg, Depth: 287 mm, Width: 625 mm, Height: 354 mm
Dimensions (dockable flatbed)	Weight: 7.3 kg, Length: 643 mm, Width: 486 mm, Height: 162.5 mm
Warranty***	12 months on-site
Warranty Enhancement***	36 months PerformancePlus on-site, 8 hrs response, consumables included

Specifications are subject to change without notice. Throughput speeds may vary depending on your choice of driver, application software, operating system and PC.

*With an optimal PC configuration (3.0 GHz processor, 512 MB RAM), the i280 model can achieve 40 ppm at 300 dpi. **Class A when optional dockable flatbed is attached.

***There may be geographical limitations to the availability of Services. For full details please contact your Reseller of Kodak products or your local Kodak Service & Support organisation.

For more information visit: www.kodak.com/go/docimaging
www.kodak.com/go/contactservice

United Kingdom, Phone: +44 870 8502351, Fax: +44 870 850 2352
Nordic and Africa, Phone: +44 1442 846547, Fax: +44 1442 846606
Germany, Austria and Switzerland, Phone: +49 711 406 2535, Fax: +49 711 406 3619
Eastern Europe, Near and Middle East, Phone: +36 1 454 3031, Fax: +36 1 387 9113
France, Spain and Portugal, Phone: +33 1 4001 4082, Fax +33 1 4001 3981
Italy, Phone: +39 0266028338, Fax: +39 0266028358
The Netherlands, Phone: +31 347 363 612, Fax: +31 347 363 606
Belgium and Luxembourg, Phone: +32 262 68506, Fax: +32 262 68502

Innovation you can count on™

© Kodak, 2006. Kodak is a trademark of Eastman Kodak Company. DoldeMedien_0119_06

CAT NO. 742 0441



As an Energy Star® Partner, Eastman Kodak Company has determined that these products meet Energy Star® guidelines for energy efficiency.